



URSA 20 (Cladding Roll)

**System/Product:**

URSA 20 (Cladding Roll) is a lightweight, non-combustible, unfaced glass mineral wool product.

Description:

It is suitable for use in a wide range of applications including roofs, walls and floors to provide thermal and acoustic insulation.

Product Information

	1062059	1062060	1062061	1062062	1075172	1075173	1075406	1075171	Unit
Product Code	*				**	**			
Thickness	60	80	100	120	140	160	180	200	mm
Width	1200	1200	1200	1200	1200	1200	1200	1200	mm
Length	12.0	10.0	8.0	6.0	5.0	5.0	5.0	4.0	m
Pack Area	14.40	12.00	9.60	7.20	6.0	6.0	6.0	4.8	m ²
Packs / pallet	24	24	24	24	24	24	24	24	
m ² / pallet	345.60	288.00	230.40	172.80	144.00	144.00	144.00	115.20	
Thermal Conductivity	0.040	0.040	0.040	0.040	0.040	0.040	0.040	0.040	W/mK
Thermal Resistance	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	m ² K/W

* Minimum order of 10 pallets

** Made to order materials. Please enquire for availability.



This product data sheet is based upon the knowledge and experience gained by URSA International in manufacturing insulation materials. It is made in good faith without any guarantee or warranty of accuracy.

URSA UK LTD, Crest House, 102-104 Church Road, Teddington, Middlesex, TW11 8PY, United Kingdom
 Tel. 020 8977 9697, Fax. 020 8977 9456, e-mail: ursauk@uralita.com